WRENCH, SPLINED EXTERNAL BEARING RETAINING, NUT, MAIN TRANSMISSION Los I guerra I co I MIN FRID HELICOPTER COMPANY ALT MATL : 4130 STL BAR, 2 3/4 DIAX 2 1/4 LG FABRICATION MAY BE ONE PIECE AND -5 PLATE OMITTED T103004 1) SEE E O 117 A A G IS G ILG FRUM MATIBIAL SPEC 4130 ALY STL COMMERICAL 274 1/2 MUL 12.0 4150 MY SIL COMMERICAL THE COOK LIGHT NO DAG NO USED TO TORQUE 222-040-228 NUT 0 97499 A HEAT TREAT TO 145,000 ~ 165,000 MATERIAL O A566-12-03 Ado Jana 300 Ma But Lyn 2 375 constant WELD PER MIL-W-8611 8 1 15 25x 2.5 x 2.5 STOCK SIZE ROCKWELL Re 32-36 MKOVICH A A CODE NOVITHCLATURE MICHIE CHERTO 11.01.1 WRENCH SPLINE NOTES PLATE DAWACI ROUGHESS PRE UNA PAR! . 1.1. TRAT MIL. H-6875 UMATES OTHERWISE SPECIFIED MAGE 4 8 'n ( PAPT OR IDENTIFYING NO T103004 - 5 T103004 - 3 T103004 UNITESS OTHERWIST SPECIFED.

1. MARK PER BES I'W ADDS

2. BEFOR ALL STARP PEDGES. OIS X-20.

3. IORQUE PER BES I'W ADIR

4. SAMETER PER BES I'W ADIR

5. DUMENSIONAL LIMITS APRIY

AFFER PATHING APPLICABLE DOCUMENTS

ABBREVIATIONS PER MIL STD 12

ABBREVIATIONS PER MIL STD 12

DIMENSIONING PER USAS 714 5

RECTRICAL SYMBOLS

FLECTRICAL REP DESIGNATIONS

FLECTRICAL REP DESIGNATIONS **⊘** 222-040-068 CASE ASSY REF - 222-340-043 BEARING REF 111-040-012 122 HEAT AUT UND ON .222-040-247 TAB LOC REF 222-040-128 NUT REF 1.542 MAJOR DIA 3 9 SPLINE -A-1.875 STOCK 040 X 040. FOR APPROVED INTERCHANGEABLE EQUIVALENTS AND SUPERSEDED PARTS -- SEE BNT STANDARD 170-001 SOURCES QUALIFIED AND APPROVED BY BHT FOR STANDARDS AND MATE-RIALS ARE LISTED IN REPORT 299-099-900. -1.75 90 2.375 DIA STOCK 1.508 1.508 1.508 P. 25 TYP SPLINE PLATE SPLINE = WRENCH PLATE EXTERNAL INVOLUTE FLAT ROOT, SIDE FIT 1.6722 ~ 2.6672 2.542 ~ 2.537 2.5000000 2.400 MIN 2.432 2.1650635 0.0858 16/32 300 NIM OLS. 8 SPLINE MIN ACTUAL (REF)
MAX ACTUAL (REF)
MEASUREMENT BETWEEN PRESSURE ANGLE
BASE CIRCLE DIA (REF)\_
PITCH DIA (REF) MAJOR DIA (REF.)
CIRCULAR SPACE WIDTH SURFACE TEXTURE SNIA PIQ OOTI NO. OF TEETH MINOR DIA TYPE PITCH